

Single-track Power Trolley (FOB china)

Type	Length (m)	Power (kw)	Orbit (kg)	Gear diameter (Φ)	Output gear	Application of the load	US \$/unit
T-0.75-120	0.75	0.4	9	120	M3	1T and less	545.45
T-1.2-150	1.2	0.4	9	150	M3	1.5T and less	636.36
T-1.5-150	1.5	0.4	9	150	M3	2T and less	757.58
T-1.8-150	1.8	0.4	9	150	M3	2T and less	909.09
T-1.2-180	1.2	0.4	12	180	M4	2T and less	909.09
T-1.8-180	1.8	0.4	12	180	M4	3T and less	1060.61
T-2.0-180	2.0	0.4	12	180	M4	3T and less	1121.21
T-2.2-180	2.2	0.4	12	180	M4	3T and less	1181.82
T-2.0-220	2.0	0.75	12	220	M4	5T and less	1181.82
T-2.2-225	2.2	0.75	12	225	M4	5T and less	1242.42
T-2.5-225	2.5	0.75	12	225	M4	5T, 7.5T and less	1242.42
T-2.2-250	2.2	0.75	15	250	M4	5T, 7.5T and less	1363.64
T-2.5-250	2.5	0.75	15	250	M4	7.5T and less	1515.15
T-3.0-250	3.0	0.75	15	250	M4	10T and less	1818.18
T-2.5-280	2.5	0.75	22	280	M5	10T and less	1818.18
T-3.0-290	3.0	1.5	22	290	M5	10T and less	2121.21
T-3.5-290	3.5	1.5	22	290	M5	15T and less	2121.21
T-2.5-300	2.5	2.2-1.5	30	300	M5	15T and less	2272.73
T-3.0-300	3.0	2.2-1.5	30	300	M5	15T and less	2424.24
T-3.5-300	3.5	2.2-1.5	30	300	M5	15T and less	2575.76