<u>Post 11</u> : Purchase of<mark>08</mark>1.6T pullers (3RN+5DN)

| Technical characteristics | OCP specifications | Proposal of vendor |
|--|--|-----------------------|
| Mark | To be specified by the supplier | |
| Reference | To be specified by the supplier | |
| Amount | 08 | |
| Ability | 1.6T | |
| Weight (kg) | 20 | |
| Dimensions | 660x330x140 | |
| Cable advance (M-Front/M-Rear) | 56/70mm | |
| Cable diameter | 11.5mm | |
| Rope breaking load daN | 8000 daN | |
| Weight | About 18kg | |
| Length of the cable equipping the puller | 20m | |
| Certificates | Nationalized Static and Dynamic Test Certificate and CE Certificate | |
| | | |
| Documentation | To provide the COMPLETE technical documentation in French | |



Post 12 : Purchase of 083.2T pullers (1RN+7DN)

| Technical characteristics | OCP specifications | Proposal of vendor |
|--|---|-----------------------|
| Mark | To be specified by the supplier | |
| Reference | To be specified by the supplier | |
| Amount | 08 | |
| Ability | 3.2T | |
| Weight (kg) | 27 | |
| Dimensions | 676x330x156 | |
| Cable advance (M-Front/M-Rear) | 30/48mm | |
| Cable diameter | 16.3mm | |
| Rope breaking load daN | 16000 daN | |
| Weight | About 27kg | |
| Length of the cable equipping the puller | 20m | |
| Certificates | Nationalized Static and Dynamic Test | |
| | Certificate and CE Certificate | |
| Documentation | To provide the COMPLETE technical documentation in French | |
| | | |



Post 13 : Purchase of042-hook 5T pullers

| Technical characteristics | OCP specifications | Proposal from vendor |
|---|--|----------------------------|
| Mark | To be specified by the supplier | |
| Reference | To be specified by the supplier | |
| Amount | 04 | |
| Tractive capacity-force | 5T | |
| Number of hooks | 2 | |
| High tensile steel construction | Yes | |
| Distance between brackets | To be specified by the supplier | |
| Non-rotating galvanized steel cable Special for strong and flexible tires | Yes | |
| Equipped with a hauling pulley | Yes | |
| The 2 hooks equipped with safety latches | Yes | |
| Hook material | Treated alloy steel | |
| Equipped with a load limiter | Yes | |
| Paint | High resistance powder RAL7021, thickness 70µ | |
| Certificates | Nationalized Static and Dynamic Test Certificate and CE Certificate | |
| Documentation | To provide the COMPLETE technical documentation in French | |

